


## Gold Balances

### Quality for all Needs



#### Balances with Swiss Technology

METTLER TOLEDO stands for Jewelry balances made in Switzerland. Our balances are built to last and designed to be accurate and reliable in even the toughest working environments. Be confident in highly reproducible weighing results.



#### JP – Jewelry Plus

High quality for demanding users, with more features as standard: fully automatic self-adjustment (FACT); a high contrast HCD display; two RS232 interfaces for simultaneous connection of an auxiliary display and printer or PC; built-in density determination software.



#### JS – Jewelry Standard

Performance with value: Manual one-keypress adjustment with built-in internal weight; legible, back-lit display; RS232 interface for connecting an auxiliary display, printer or PC.



#### JL – Jewelry Light

Accuracy and quality combined with the need for compactness and affordability: the JL balances are at home in jewelry shops and other retail applications, where simplicity and ease of use matter most.



#### The Best Choice for Weighing Precious Metals

Weight is all-important in the gold trade, so a good, solid weighing instrument is essential: a balance that simply works as it should, delivering accurate and trustworthy results every time, under all operating conditions.

Designed to meet every need, the range includes models for everyday use by goldsmiths, jewelry manufacturers and retailers, high-precision models for assay offices and hallmarking, and a high-capacity line for weighing larger quantities in manufacturing and inventory taking. Specifications differ between models, but the range shows consistent hallmarks: easy and straightforward operation, a large weighing pan, plus bright and clear display of weighing results.

# Gold Balances – Model overview



Readability	Model	Capacity	Repeatability	Pan size (mm)	Interfaces	Calibration
0.01 mg / 0.1 mg	JP105DUG	42 g / 120 g	0.01 mg / 0.1 mg	∅ 80	RS232, USB	FACT
0.001 g	JP303G	320 g	0.001 g	∅ 120	2 x RS232	FACT
	JP503G	520 g	0.001 g	∅ 120	2 x RS232	FACT
0.01 g	JP802G	820 g	0.01 g	170 x 190	2 x RS232	FACT
	JP2002G	2200 g	0.01 g	170 x 190	2 x RS232	FACT
	JP3002G	3200 g	0.01 g	170 x 190	2 x RS232	FACT
	JP4002G	4200 g	0.01 g	170 x 190	2 x RS232	FACT
	JP6002G	6200 g	0.01 g	170 x 190	2 x RS232	FACT
0.1 g	JP8001G	8200 g	0.1 g	170 x 190	2 x RS232	FACT
	JP16001G	16200 g	0.1 g	351 x 245	RS232, USB	FACT
	JP32001G	32200 g	0.1 g	351 x 245	RS232, USB	FACT
0.001 g	JS303G	320 g	0.001 g	∅ 120	RS232	Int. Cal
	JS503G	520 g	0.001 g	∅ 120	RS232	Int. Cal
0.01 g	JS802G	820 g	0.001 g	170 x 190	RS232	Int. Cal
	JS2002G	2200 g	0.01 g	170 x 190	RS232	Int. Cal
	JS3002G	3200 g	0.01 g	170 x 190	RS232	Int. Cal
	JS4002G	4200 g	0.01 g	170 x 190	RS232	Int. Cal
	JS6002G	6200 g	0.01 g	170 x 190	RS232	Int. Cal
0.1 g	JS8001G	8200 g	0.1 g	170 x 190	RS232	Int. Cal
0.01 g	JL602-G/L01	610 g	0.01 g	∅ 120	RS232	Ext. Cal
	JL1502-G/01	1510 g	0.01 g	∅ 160	RS232	Ext. Cal
0.1 g	JL6001-G/L01	6100 g	0.1 g	∅ 160	RS232	Ext. Cal

## Features

<div style="border: 1px solid #ccc; padding: 5px; margin-bottom: 10px; text-align: center;"><b>FACT</b></div> <div style="border: 1px solid #ccc; padding: 5px; margin-bottom: 10px; text-align: center;"><b>Cal Int</b></div> <div style="border: 1px solid #ccc; padding: 5px; margin-bottom: 10px; text-align: center;"><b>Cal Ext</b></div> <div style="border: 1px solid #ccc; padding: 5px; text-align: center;"><b>31</b></div>	<p><b>FACT</b> Fully automatic time- and temperature controlled internal adjustment (JP models)</p> <p><b>Internal Adjustment</b> On demand, at a key press with an internal weight (JS models)</p> <p><b>External Adjustment</b> On demand, at a key press with an external weight (JL models)</p> <p><b>Date and Time</b> Built-in time and date function (JP, JS)</p>	<div style="border: 1px solid #ccc; padding: 5px; margin-bottom: 10px; text-align: center;"><b>PC direct</b></div> <div style="border: 1px solid #ccc; padding: 5px; margin-bottom: 10px; text-align: center;"><b>Battery Operation</b></div> <div style="border: 1px solid #ccc; padding: 5px; margin-bottom: 10px; text-align: center;"><b>Below Weighing</b></div> <div style="border: 1px solid #ccc; padding: 5px; text-align: center;"><b>Protective Cover</b></div>	<p><b>PC direct</b> Transfer weighing data to a PC without additional software (JP, JS)</p> <p><b>Battery Operation</b> Full independence from power supply for 8 hours (not JP105DUG, JP16001G, JP32001G)</p> <p><b>Below Weighing</b> Hook for weighing below the balance</p> <p><b>Protective Cover</b> Protects the balance from stains and scratches</p>
--	--	--	---

## Approval

Approved versions of all models in most countries available

## Units

ct, g, mg, kg, pound, ounce, troy ounce, grain, penny-weight, momme, mesghal, Hong Kong tael, Singapore tael, Taiwan tael, tical, tola, Baht (subject to country regulations)

## Applications

JP: Density, Check Weighing, Statistics, Totaling, Recall, Piece Counting, Percent Weighing, Free Factor, Diagnostics  
 JS: Check Weighing, Statistics, Totaling, Recall, Piece Counting, Percent Weighing, Free Factor, Diagnostics  
 JL: Piece Counting, Percent Weighing, Free Factor

## Accessories

Accessories		Order No.
Density Kit	For JP105DUG	30004077
	For JP303G, JP503G, JS303G, JP503G	11142144
Compact Printer	RS-P25	11124300
Auxiliary Display	AD-RS-J7 for JP, JS	12122380
	RS-AD-7 for JL	72213564
Transport Case	For JP, JS with pan size 170 x 190 mm	11124240
	For JL	12102982
	For JP105DUG	30006317
PowerPac	PowerPac-M-12V	12122363
Draft shield	For JP, JS with pan size 170 x 190 mm	12121015
LabX Direct Balance	Data management PC software	11120340



## Mettler-Toledo AG

Laboratory & Weighing Technologies  
 CH-8606 Greifensee, Switzerland  
 Tel. +41 44 944 22 11  
 Fax +41 44 944 30 60



Subject to technical changes  
 © 02/2011 Mettler-Toledo AG  
 Printed in Switzerland 30008219  
 Global MarCom Switzerland

[www.mt.com/jewelry](http://www.mt.com/jewelry)

For more information